

# HTB-230D-R680E

AI box PC with 10.1" touch panel and 13th generation Intel® Core™ i9 processor



## Features

- » Intel® Core™ i9 processor
- » 10.1" front panel with P-CAP touch
- » Expansion slots for GPU and add-on cards
- » Compatible to Nvidia Quadro RTX Ampere series GPU
- » Support M.2 Gen4 x4 NVMe SSD
- » Support 4 x DDR5

## Specifications

<b>Display</b>	
LCD Size	10.1"
LCD Resolution	1920 x 1200
LCD Brightness (cd/m <sup>2</sup> )	600
LCD Contrast Ratio	900:1
LCD Color	16.7M (8-bit)
LCD Pixel Pitch (mm)	0.03764 x 0.11292
LCD Viewing Angle (H-V)	160°/160°
Touch Screen	Projected capacitive type with 10-point multi-touch
Touch Controller	ILI
Touch Surface Hardness	6H
<b>System</b>	
Processor	Intel® Core™ i9 processor
Chipset	Intel® R680E
GPU	Compatible with NVIDIA Quadro RTX Ampere series GPU
<b>Network</b>	
Ethernet Controller	Intel® I225-V
<b>Storage</b>	
Storage	M.2 2280 NVMe Gen4 x4 SSD
RAM	4 x 288-pin dual-channel DDR5 U-DIMM, up to 4400MHz, ECC & non-ECC un-buffered memory (system max. 128GB)
<b>Expansion Slots</b>	
Expansion Slots	1 x PCIe Gen4 x16 slot for GPU
	2 x PCIe Gen4 x4 slot for add-on cards
	1 x M.2 2280 PCIe Gen4 x4 M key slot for SSD
<b>Audio</b>	
Speaker	2 x 3W speaker
<b>I/O Interface</b>	
Front I/O	2 x USB 3.2 Gen 2
Rear I/O	1 x HDMI output
	1 x AC IN
	1 x Speaker
	1 x Microphone

	2 x 2.5 GbE LAN
	4 x USB 3.2 Gen 2
<b>Indicator&amp;Buttons</b>	
Buttons	1 x System power button (with power LED)
	1 x Power supply swich
Indicators	Power LED
<b>Physical Characteristics</b>	
Color	White
Thermal	Smart fan
Construction Material	NCT(N); SECC
Weight (Net) (kg)	7.68
Dimensions (LxWxH) (mm)	310 x 203 x 390
<b>Power</b>	
Input	115V AC – 264V AC medical grade ATX power
Output	700W medical power adapter
<b>Environment</b>	
Operating Temperature	0°C ~ 40°C
Storage Temperature	-20°C ~ 65°C
Humidity	10% – 95% (non-condensing)
Vibration	1G
Operating Shock	5G peak acceleration (11ms duration)
Non-operating shock	15G peak acceleration (11ms duration)
<b>Certifications</b>	
Safety & EMC	CE,
	FCC Class B Part18,
	UL 60601-1,
	IEC/EN 60601-1,
	IEC/EN 60601-1-2

## Ordering Information

HTB-230D-R680E-R10	Medical AI Box PC, 10.1" panel, PCAP touchscreen, w/o CPU, w/o GPU card, w/o DDR5, w/o M.2 SSD, one PCIe Gen 4 x16 slot, two PCIe Gen 4 x4 slots, 700W medical power adapter, R10, RoHS
--------------------	---

## Packing List

1 x European power cord (183 cm, C13)	
---------------------------------------	--