

# 63010-010600-010-RS

600 W PS/2 ATX Power Supply with ErP



## Features

600 W PS/2 ATX Power Supply with ErP

## Specifications

Input	
Voltage	90~264 VAC Full Range
Frequency	47 Hz ~ 63 Hz
Input Current	8A (RMS)@115VAC, 4A (RMS)@230VAC
Inrush Current	40A max. for 115VAC, 80A max. for 230VAC
Output	
Voltage	+3.3V/25A,+5V/25A,+12V1/16A,+12V2/16A,+12V3/16A,+12V4/16A,-12V/0.5A,+5Vsb/4A,-5V/0.5A
Over Voltage Protection	+3.3V: 3.9V-4.5V +5V: 5.7V-6.5V +12V1 ~ +12V4: 13.3V-16.7V
Short Circuit Protection	+3.3V, +5V, +12V1, +12V2, +12V3, +12V4, 24V or -12V shutdown and latch off
General	
Watt	600
Efficiency	82%
MTBF	100000
Operating temperature	0°C ~ 50°C
Storage temperature	-20°C ~ 80°C
Dimensions	140 x 150 x 86
Output Connector	1 x 20+4-pin ATX, 2 x 4-pin 12V CPU, 9 x HDD/CDROM, 1 x Graphics card power, 2 x FDD,2 x SATA

## Ordering Information

63010-010600-010-RS	PS/2 Power;FSP;FSP600-80PSA(SK);9PA6009824;Active PFC;Vin:90~264VAC;600W;150*140*86mm;;;meet 80plus(BRONZE);Vout:ATX;ATX;CCL;RoHS
---------------------	---