


# 63010-010400-010-RS

400 W PS/2 ATX Power Supply with ErP



## Features

## Specifications

| Input                    |   |
|--------------------------|---|
| Voltage                  | 90~264 VAC Full Range   |
| Frequency                | 47 Hz ~ 63 Hz   |
| Input Current            | 5A (RMS)@115VAC, 2.5A (RMS)@230VAC  |
| Inrush Current           | 80A max. for 115VAC, 160A max. for 230VAC   |
| Output                   |   |
| Voltage                  | +3.3V/21A, +5V/16A, +12V1/16A, +12V2/17A, -12V/0.5A, +5Vsb/3A, -5V/0.1A                                       |
| Over Voltage Protection  | +3.3V: 3.76V-4.3V<br>+5V: 5.74V-7.0V<br>+12V1 and +12V2: 13.4V-15.6V  |
| Short Circuit Protection | +3.3V, +5V, +12V or -12V shutdown and latch off   |
| General                  |   |
| Watt                     | 400   |
| Efficiency               | 87%   |
| MTBF                     | 100000  |
| Operating temperature    | 0°C ~ 50°C  |
| Storage temperature      | -20°C ~ 80°C  |
| Dimensions               | 140 x 150 x 86  |
| Output Connector         | 1 x 20+4-PIN ATX,<br>2 x 4-pin 12V CPU,<br>8 x HDD/CDROM,<br>1 x Graphics card power,<br>2 x FDD,<br>2 x SATA |

## Ordering Information

|                     |   |
|---------------------|---|
| 63010-010400-010-RS | PS/2 Power;FSP;FSP400-70AGGBM;9PA400CH06;Active PFC;Vin:90~264VAC;400W;;;meet 80plus(GOLD),with ERP & on/off switch;Vout:ATX;ATX;CCL;RoHS |
|---------------------|---|