

# DM-F08A

6.5"~15" DM-F IP65 Industrial Monitor



## Features

- » Robust IP65 aluminum front bezel
- » Aesthetic ultra-thin bezel for seamless panel mount installation
- » DC input
- » DVI / VGA flexible video input solution
- » Resistive single touch
- » Wide temperature support

## Specifications

Display	
Backlight MTBF(hrs)	50000
Brightness(cd/m2)	500
Contrast Ratio	20.8340277777778
LCD Size	8"(4:3)
Max Resolution	800 (W) x 600 (H)
Environment	
Humidity	10% to 95% (non-condensing)
IP Level	IP 65 compliant front panel
Operating Temperature	-20°C ~ 60°C (with air flow)
Storage Temperature	-20°C ~ 70°C
I/O Interface	
I/O Ports and Switches	1 x VGA (DB-15)
	1 x DVI
	1 x USB 2.0 (touch)
	1 x RS-232 (reserved for resistive touch ATO)
	1 x Lockable 12V DC jack
LCD	
LCD Color	262K
Pixel Pitch (mm)	0.0675 x 0.2025
Viewing Angle (H-V)	140°/120°
Physical Characteristics	
Cutout Dimensions	206 x 154
Dimensions (LxWxH) (mm)	222.2 x 182.2 x 42.7
Power	
Power adapter	12V DC
Touch	
Touch Controller	Penmount 6000
Touch Screen	5-wire resistive single touch window
Weight	

Weight	1.33/4.5
--------	----------

## Ordering Information

---

DM-F08A/R-R10	8" 500 cd/m <sup>2</sup> SVGA LCD monitor, Aluminum front panel, Black color, W/ USB resistive touch screen, 12V DC input, R10
---------------	--

## Packing List

---

1 x Touch Pen	1 x USB Cable
1 x VGA Cable	1 x Adapter
1 x AC power cord	