

PuIM-100G2SF

Intel® Ethernet Controller EZE810CAM2 based Network Interface Card with 2 x QSFP28 by 1 PCIe 4.0 x8 interface



Features

- » 1 x Intel E810 Ethernet controller
- » 2 ports 100GbE QSFP28 connector
- » 1 x PCIe 4.0 x8
- » RoHS/CE/FCC compliant

Specifications

| | |
|-----------------------------|---------------------------------------|
| System | |
| CPU | Intel® Ethernet Controller E810 |
| Cooling method / System Fan | Active Fan |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 165.50 (L) x 77.8 (W) x 44.2 (H) |
| I/O Interface | |
| Ethernet | 2 x LAN: 2 x QSFP28 |
| Environment | |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Storage Temperature | -20°C ~ 75°C (-4°F ~ 167°F) |
| Humidity | 5% ~ 90% RH, Non-condensing |
| Certifications | |
| Safety & EMC | RoHS |
| Card Slot Interface | |
| PCIe | 1 x PCIe Gen4 x8 |
| Card Features | |
| Speed | 100 GbE |
| Controller Chip | Intel® Ethernet Controller EZE810CAM2 |

Ordering Information

| | |
|-----------------------|---|
| PuIM-100G2SF-E810-R10 | Intel® Ethernet Controller EZE810CAM2 based Network Interface Card with 2 x QSFP28 by 1 PCIe 4.0 x8 interface |
|-----------------------|---|

Packing List

| | |
|----------------------------|---------|
| 1 x PuIM-100G2SF-E810 card | 1 x QIG |
|----------------------------|---------|