

ACE-A130B

300 W PS/2 ATX Power Supply with ErP



Features

300 W PS/2 ATX Power Supply with ErP

Specifications

| General | |
|--------------------------|--|
| Dimensions | 140 x 150 x 86 |
| Efficiency | 85% |
| MTBF | 100,000 |
| Operating temperature | -5°C ~ 50°C |
| Output Connector | 1 x 20-pin ATX, 1 x 4-pin 12V CPU, 6 x HDD/CDROM, 1 x FDD, 1 x Extra +5V (P10), 2 x SATA |
| Storage temperature | -40°C ~ 70°C |
| Watt | 300W |
| Input | |
| Voltage | 90~264 VAC Full Range |
| Frequency | 47 Hz ~ 63 Hz |
| Input Current | 6A (RMS)@115VAC, 3A (RMS)@230VAC |
| Inrush Current | 80A max. for 115VAC, 160A max. for 230VAC |
| Output | |
| Voltage | +3.3V/19A,+5V/16A,+12V1/17A,+12V2/17A,-12V/0.3A,+5Vsb/3A,-5V/0.2A |
| Over Voltage Protection | +3.3V: 3.7V-4.8V |
| | +5V: 5.7V-7.0V |
| | +12V1 and +12V2: 13.3V-16V |
| Short Circuit Protection | +3.3V, +5V, +12V or -12V shutdown and latch off |

Ordering Information

| | |
|-----------------|--|
| ACE-A130B-S-R10 | 300W PS/2 ATX Power Supply with ERP/PFC & on/off switch,CCL;RoHS |
| ACE-A130B-R10 | 300W PS/2 ATX Power Supply with ERP& PFC,CCL;RoHS |