

TANK-600-D2550/N2600

无风扇嵌入式系统，Intel® Cedarview 双核 Atom™ CPU



Features

- » Intel® Atom™ D2550 1.86 GHz 双核处理器 / Intel® Atom™ N2600 1.6 GHz 双核处理器
- » 八个 COM 端口: 六个 RS-232 和 两个 RS-232/422/485
- » 6 x USB 2.0
- » 用于高速网络应用的双 PCIe GbE LAN

Specifications

颜色	
颜色	Black C + Silver
尺寸	
尺寸	193.4 x 200 x 57
运行环境	
湿度	5% ~ 95%, non-condensing
操作温度	-20°C ~70°C with air flow (SSD),
扩展插槽	
扩展插槽	1 x Full size (co-lay mSATA)
	1 x Half size
形态系数	
SBC 形态系数	CPU:
	Intel® Atom™ D2550 1.86 GHz
	Intel® Atom™ N2600 1.6 GHz
	Chipset: Intel® NM10
	System Memory:
	On-board DDR3 4/2 GB
I/O 接口	
I/O 端口	6 x USB 2.0
	Ethernet:
	2 x RJ-45
	PCIe GbE by Realtek 8111E
	COM Port
	6 x RS-232 (DB-9)
	2 x RS-232/422/485 (DB-9)
	Display: 1 x VGA
	1 x Line-out, 1 x Mic-in
系统	
散热方式 / 系统风扇	Fanless
驱动仓	1 x 2.5' SATA 3Gb/s HDD/SSD bay
重量	
重量	2.2 kg/3 kg

Ordering Information

TANK-600-CV-N2600-8C/2G-R11	Extend temperature Fanless embedded system with Intel® Cedarview N2600 1.6 GHz processor dual core CPU, with 2G DDR3 RAM onboard, 1xVGA, Dual GbE LAN, 6xUSB2.0 , 2xRS-232/422/485 , 6 x RS-232, RoHS
TANK-600-CV-D2550-8C/4G-R11	Extend temperature Fanless embedded system with Intel® Cedarview D2550 1.86GHz processor dual core CPU, with 4G DDR3 RAM onboard, 1xVGA, Dual GbE LAN , 6xUSB2.0 , 2xRS-232/422/485 , 6 x RS-232, RoHS

Packing List

1 x 电源线	1 x 电源适配器 (符合 PSE & ErP)
1 x 壁挂式支架	1 x 螺丝钉