

WS-855GS

15" IP 64 Waterproof Workstation: Robust, Shock Resistance



Features

- » Die-cast aluminum front panel with integrated LCD screen
- » New robust chassis and retention kit structure for shock and vibration
- » Front panel, membrane keys, mouse pad and drive-bay enclosure meet IP 64 standard for tough environment
- » Full function membrane keys and submerged OSD controller
- » Advanced thermal and air-flow design
- » Analog VGA interface supports all CPU boards

Specifications

| | |
|-----------------------|-------------------------------|
| Dimensions | |
| Dimensions | 483 x 353 x 261 |
| Environment | |
| Humidity | 10%~95%, non-condensing |
| Operating Temperature | 0°C ~ 50°C |
| Storage Temperature | -10°C ~ 60°C |
| Function Key | |
| Function Key | 10 Keys |
| KeyPad | |
| KeyPad | 59 Keys |
| LCD | |
| Backlight MTBF | 70000 (LED Backlight) |
| Brightness (cd/m2) | 450 |
| Contrast Ratio | 800:1 |
| LCD Color | 16.2M |
| Resolution | 1024 x 768 |
| Size | 15" |
| Touch | |
| Touch Screen | 5-wire resistive touch screen |
| Weight | |
| Weight | 12 kg / 18.2 kg |

Ordering Information

| | |
|-------------------------|--|
| WS-855GSATX/A130B/R-R40 | 8U m-ATX 15" 450cd/m ² XGA LCD workstation with ACE-A130B-R10 300W ATX with PFC power supply and 15" resistive touch screen, M-ATX version, RoHS, R40 |
| WS-855GS/A130B/R-R40 | 8U 15" 450cd/m ² XGA LCD 10-slot industrial workstation with ACE-A130B-R10 300W ATX with PFC power supply and 15" resistive touch screen, RoHS, R40 |

Packing List

| | |
|--|---|
| 1 x AC Power Cable | 1 x VGA Cable |
| 1 x PS_ON Cable for ATX signal | 4 x Press Stick Kit (Long) |
| 3 x Press Stick Kit (Short) | 7 x Press Stick Rubber |
| 1 x User Manual | 1 x KeyPad / MousePad PS/2 Cable (For SBC Models) |
| 1 x KeyPad / MousePad PS/2 Cable (For m-ATX (Motherboards) Models) | 1 x RS-232 Cable / Touch Pen for Touch Screen |