

# DM-F08A

6.5"~15" DM-F IP65 Industrial Monitor



## Features

- » Robust IP65 aluminum front bezel
- » Aesthetic ultra-thin bezel for seamless panel mount installation
- » DC input
- » DVI / VGA flexible video input solution
- » Resistive single touch
- » Wide temperature support

## Specifications

Display	
LCD Size	8"(4:3)
Brightness(cd/m2)	500
Max Resolution	800 (W) x 600 (H)
Contrast Ratio	500:1
Backlight MTBF(hrs)	50000
I/O Interface	
I/O Ports and Switches	1 x VGA (DB-15)
	1 x DVI
	1 x USB 2.0 (touch)
	1 x RS-232 (reserved for resistive touch ATO)
	1 x Lockable 12V DC jack
Power	
Power adapter	12V DC
Environment	
工作温度	-20°C ~ 60°C (with air flow)
相对湿度	10% to 95% (non-condensing)
存储温度	-20°C ~ 70°C
IP Level	IP 65 compliant front panel
Physical Characteristics	
尺寸 (LxWxH) (mm)	222.2 x 182.2 x 42.7
Cutout Dimensions	206 x 154
Weight	
Weight	1.33/4.5
LCD	
LCD 色彩	262K
像素间距 (mm)	0.0675 x 0.2025
可视角度 (H-V)	140°/120°
Touch	
触摸屏	5-wire resistive single touch window

触控IC

Penmount 6000

## Ordering Information

---

DM-F08A/R-R21

8" 500 cd/m<sup>2</sup> SVGA LCD monitor, Aluminum front panel, Black color, W/ USB resistive touch screen, 12V DC input, Powder paint, R21

## Packing List

---

1 x Touch Pen

1 x USB Cable

1 x VGA Cable

1 x Adapter

1 x AC power cord