

iRIS2-2620

IPMI 2.0 adapter card with 2620 BMC chip for IEI IRIS2 Connector IPMI 2.0 module



Features

- » IPMI 2.0 based remote management
- » Out-of-Band management
- » Hardware health monitor
- » Virtual media
- » Remote power control

Specifications

| | |
|-----------------|---|
| 尺寸类型 | |
| 尺寸类型 | IEI IRIS2 Connector |
| 物理特性 | |
| 尺寸 (LxWxH) (mm) | 30mm x 80mm x 7.6mm |
| 净重 | 18g |
| I/O 接口 | |
| 显示输出 | Display Port : Display Port Connector |
| 网络 | 描述: : 10/100/1000Mbps |
| Other Features | |
| iRIS | --- IPMI 2.0 Based Management --- |
| | » BMC stack with a full IPMI 2.0 implementation |
| | » Customizable sensor management |
| | » OS Platform Independent |
| | --- Hardware Health Monitor --- |
| | » System/CPU temperature |
| | » Fan speeds |
| | » Voltage |
| | » Chassis intrusion |
| | » Power supply failed |
| | » FRU (Field Replaceable Unit) |
| | --- Event Log --- |
| | » BIOS event |
| | » Hardware health monitor event |
| | » Sensor readings |
| | --- LDAP Support --- |
| | » Direct LDAP support from the device |
| | » Open LDAP (Generic LDAP) supported |
| | --- Media Redirection --- |
| | » Virtual Media allows users to remotely mount given ISO/IMG drive images through BMC to Server |

| | |
|----------|--|
| | » Support for USB key |
| | --- Remote Power Control --- |
| | » Remote power control |
| | » Serial over LAN (SOL) |
| | --- User Management --- |
| | » IPMI based user management |
| | » Added security with SSL (HTTPS) |
| | » Multiple user permission level |
| | » Multiple user profiles |
| | --- Web-based Configuration --- |
| | » Full configuration using web UI |
| | » Fail-safe firmware upgrade |
| | » Multi-language support in web interface with English as the currently supported language |
| 环境 | |
| 操作温度 | -10°C ~ 60°C |
| Humidity | 5% ~95%, non-condensing |

Ordering Information

| | |
|----------------|---|
| iRIS2-2620-R10 | IPMI 2.0 adapter card with AST2620 BMC chip for iEi iRIS2 Connector IPMI 2.0 module |
|----------------|---|

Packing List

| | |
|--------------------------------------|--|
| 1 x iRIS2-2620 IPMI 2.0 adapter card | |
|--------------------------------------|--|