

IOVU-751R

7" TFT WVGA LCD with resistive touchscreen



Features

- » 7" TFT WVGA LCD with resistive touchscreen
- » Alchemy™ AU1250 500 MHz CPU
- » Powered by Windows® CE 5.0
- » Built-in Ethernet LAN
- » Built-in RS-232/422/485 Port
- » Supports Power over Ethernet (PoE)
- » Multimedia support for MPEG 1/2/4 and WMV9

Specifications

| | |
|--------------------------|---|
| Environment | |
| Operating Temperature | -20°C~60°C |
| LCD | |
| Brightness (cd/m2) | 500 |
| Resolution | WVGA |
| Size | 7" |
| Viewing Angle (H-V) | 140° / 100° |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 226 x 140 x 41 |
| Net Weight | 0.8 Kg |
| Power | |
| Power adapter | 9-30V DC input |
| Power consumption | Max. 14W |
| System | |
| CPU | Alchemy™ AU1250 500 MHz |
| Memory Ext. | 256 MB DDR2 |
| On-board Memory | 2MB |
| Touch | |
| Touch Screen | Resistive Type |
| I/O Interface | |
| I/O Interface | 2 x Speaker(1.5W) |
| | 1 x Reset Button |
| | 1 x RS-422/485 |
| | 1 x RS-232 |
| | 1 x Power Switch |
| | 12 x Power In(jack/terminal block DC input) |
| | 2 x LAN(10/100Mbps) |
| | 2 x USB 2.0 |

Ordering Information

IOVU-751R-CE5/-R10

E206,RISC LCD PC 8.4"以下,7" RMI ALCHEMY AU1250 500MHZ PANEL PC,WITH POE
FUNCTION,WIN CE5.0 OS,RoHS