

# uIBX-210-CV-N2600

Fanless Embedded System with Intel® Atom™ N2600 1.6 GHz, Intel® NM10 Chipset, 2 GB DDR3 Memory



## Features

- » Slim and compact embedded system design with 3rd Gen Intel® Atom™ N2600 dual-core processor, supports DDR3 memory (system max: 2 GB)
- » 12V only single voltage design, supports AT/ATX power mode selection
- » Flexible VGA and HDMI™ with dual-display support
- » Supports PCIe Mini card slot
- » Fully I/O with four USB, one VGA, one HDMI™, three COM and audio

## Specifications

<b>Color</b>	
Color	Silver
<b>Dimensions</b>	
Dimensions	146.6 x 132 x 45.2
<b>Environment</b>	
Humidity	5% ~ 95%, non-condensing
Operating Temperature	0°C ~50°C with air flow (mSATA)
<b>Expansion Slots</b>	
Expansion Slots	PCIe Mini 1 x Full size (reserved for Wi-Fi module)
<b>Form factor</b>	
SBC Form Factor	CPU: Intel® Atom™ N2600 1.6 GHz Chipset: Intel® NM10 System Memory: 1 x 204-pin DDR3 SO-DIMM (system max: 2 GB) Pre-installed 2 GB
<b>I/O Interface</b>	
I/O Ports	4 x USB 2.0 Ethernet: 1 x RJ-45 1 x PCIe GbE by Realtek 8111E RS-232: 2 x DB-9 RS-422/485: 1 x RJ-45 Display: 1 x VGA, 1 x HDMI™ Resolution: VGA: Up to 1920 x 1200 HDMI™: Up to 1920 x 1080 Audio: 1 x Line-out, 1 x Mic-in Wireless: 1 x 802.11b/g/n (optional)
<b>System</b>	
Cooling method / System Fan	Fanless
Drive Bays	1 x 2.5" SATA HDD bay
<b>Weight</b>	
Weight	980 g/1.8 kg

## Ordering Information

uIBX-210-CV-N2600/2GB-R11	Fanless embedded system with Intel Atom N2600 DC 1.6GHz, Intel NM10 chipset, single-channel 2GB DDR3 800MHZ, 12VDC-In, with 36W power adaptor, black
---------------------------	--

## Packing List

1 x uIBX-210-CV-N2600-R10	1 x Adaptor 12V/5A
1 x Screw set	1 x QIG (Quick Installation Guide)