

# TANK-6000-C226

Support IPMI 2.0 via IEI iRIS solution, Intel® E3 1225 v3/i3 4330 high performance CPU



## Features

- » Workstation with Intel® C226 chipset
- » Intel® E3 1225 v3/i3 4330 high performance CPU
- » Support two PCIe by 8 expansion cards
- » 4 x LAN port (two SFP fiber combo ports)
- » 3 x 2.5" HDD/SSD bay
- » Support IPMI 2.0 via IEI iRIS solution
- » Support programable OLED display module

## Specifications

|                             |   |
|-----------------------------|---|
| <b>Color</b>                |   |
| Color                       | Black   |
| <b>Dimensions</b>           |   |
| Dimensions                  | 310 x 199.5 x 112   |
| <b>Environment</b>          |   |
| Humidity                    | 5% ~ 95%, non-condensing  |
| Operating Temperature       | -20°C ~ 55°C with air flow (SSD)                                |
| <b>Expansion Slots</b>      |   |
| Expansion Slots             | PCIe:2 x PCIe x8 (Gen 3)  |
| <b>Form factor</b>          |   |
| SBC Form Factor             | CPU:  |
|                             | Intel® Xeon® E3 1225-v3 3.2 GHz                                 |
|                             | Intel® Core™ i3 4330 3.5 GHz                                    |
|                             | Chipset: Intel® C226  |
|                             | System Memory:  |
|                             | 4 x 240-pin DDR3 U-DIMM, 4 GB pre-installed (system max: 32 GB) |
| <b>I/O Interface</b>        |   |
| I/O Ports                   | 4 x USB 3.0   |
|                             | 2 x USB 2.0   |
|                             | Ethernet:   |
|                             | 4 x RJ-45   |
|                             | 1 x PCIe GbE by Intel® i217 PHY                                 |
|                             | 3 x PCIe by GbE Intel® i210                                     |
|                             | Fiber:  |
|                             | 2 x Combo (SFP Fiber/RJ-45), combo with LAN 1/LAN 2             |
|                             | COM Port: 2 x RS-232 (DB-9)                                     |
|                             | Display: 1 x HDMI™, 1 x VGA                                     |
|                             | Resolution:   |
|                             | HDMI™: Up to 1920 x 1200@60Hz                                   |
|                             | VGA: Up to 1920 x 1200@60Hz                                     |
|                             | Audio: 1 x Line-out, 1 x Mic in                                 |
| <b>System</b>               |   |
| Cooling method / System Fan | 92 mm x 92 mm x 25 mm   |
| Drive Bays                  | 3 x 2.5' SATA 6Gb/s HDD/SSD drive bay                           |

|        |               |
|--------|---------------|
| Weight |               |
| Weight | 2.5 kg/4.6 kg |

## Ordering Information

|                           |  |
|---------------------------|--|
| TANK-6000-C226i-i3/4G-R11 | Embedded System with Intel C226 chipset, Intel dual-core i3- 4330 3.5GHz ,TDP 54W,OLED indicator, 2 x PCIe by 8 expansion, 3 x 2.5" SATA HDD bay,DDR3 U-DIMM 4GB pre-installed ( 2 x 2GB), iRIS-2400 supported, 19/24V DC,RoHS         |
| TANK-6000-C226i-E3/4G-R11 | Embedded System with Intel C226 chipset, Intel quad-core Xeon E3-1225 v3 3.2GHz ,TDP 84W,OLED indicator, 2 x PCIe by 8 expansion, 3 x 2.5" SATA HDD bay,DDR3 U-DIMM 4GB pre-installed (2 x 2GB) , iRIS-2400 supported, 19/24V DC, RoHS |

## Packing List

|  |                    |
|--|--------------------|
| 1 x Power Adapter (With PSE & ErP Certified) | 1 x Wall mount kit |
| 1 x Screw pack                               |                    |