

# INOX-F15C-ULT3

Intel® Core™ i5 and Celeron® ULT Processor



## Features

- » 15" fanless panel PC with Intel® Skylake ULT processor
- » IP69K high pressure, high temperature protection
- » SUS304 stainless steel housing
- » Operating temperature : -20°C ~ 50°C
- » Flat glass PCAP touch with 6H hardness, resistive touch window
- » Accessible HDD Bay
- » M12 connections

## Specifications

Dimensions	
Dimensions	414 x 328.4 x 51.9
Display	
Backlight MTBF(hrs)	70000
Brightness(cd/m2)	450
Contrast Ratio	800:1
LCD Size	15"
Max Resolution	1024x768
Environment	
IP Level	IP69K
Operating Temperature	-20°C ~ 50°C
Storage Temperature	-30°C ~ 60°C
Expansion Slots	
Expansion Slots	1 x Full-size PCIe Mini card slot (SATA 6Gb/s)
	1 x Full-size/half-size (PCIe x1 and USB 2.0 signals)
	1 x M.2 B-key slot (2242/2260/2280 with USB 3.0, PCIe x2 and SATA signals)
I/O Interface	
Ethernet	2 x PCIe GbE by Intel® I210 controller
Power	
Power adapter	60W/12V waterproof power adapter
	VAC:90V~264V; 12V/5A; 60W
Power consumption	43W
Power Requirement	9-36V DC
System	
Chipset	Intel® Skylake ULT
CPU	6th generation Intel® Core™ i5 and Celeron® ULT processor
Memory Ext.	4GB
Memory Max.	32GB
Storage	1 x 2.5" SATA SSD bay
	1 x mSATA
	1 x M.2 B-key (2242/2260/2280)

I/O Interface	
I/O Interface	1 x DC Input Jack(5-pin M12)
	2 x LAN(8-pin M12 X-Code)
	1 x Power Switch
	2 x RS-232(8-pin M12)
	2 x USB 2.0(8-pin M12)

## Ordering Information

INOX-F15C-ULT3-i5/PC/4G-R10	15" 450cd/m <sup>2</sup> XGA fanless Stainless panel PC with Intel® 14nm 6th Generation Mobile Core™ i5-6300U (15W) on-board Processor (ULT), 1*4GB DDR4 RAM, PCAP touch, R10
INOX-F15C-ULT3-C/PC/4G-R10	15" 450cd/m <sup>2</sup> XGA fanless Stainless panel PC with Intel® 14nm 6th Generation Mobile Celeron®3955U (15W) on-board Processor (ULT), 1*4GB DDR4 RAM, PCAP touch, R10

## Packing List

1x Power Cable	1x Touch Pen(Resistive Touch only)
----------------	------------------------------------