

PuIM-10G4SF

Intel® Ethernet Controller XL710-BM1 based Network Interface Card with four 10GbE Fiber ports, two pair Bypass.



Features

- » 1 x Intel® Ethernet Controller XL710-BM1
- » 4 x Fiber LC (SR or LR) interface
- » PCIe 3.0 x8
- » Two LAN bypass model available

Specifications

Physical Characteristics	
Dimensions (LxWxH) (mm)	165.50 x 77.8 x 44.2
I/O Interface	
Ethernet	4 x Fiber (Fiber LC (SR or LR))
Fault-tolerance	
LAN Bypass	Yes
Environment	
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20°C ~ 75°C (-4°F ~ 167°F)
Humidity	5% ~ 90% RH, Non-condensing
Certifications	
Safety & EMC	RoHS
Card Slot Interface	
PCIe	PCIe 3.0 x8
Card Features	
Speed	1GbE/10GbE
Controller Chip	Intel® Ethernet Controller XL710-BM1

Ordering Information

PuIM-10G4SF-XL710-BP-R10	Intel® Ethernet Controller XL710-BM1 based Network Interface Card with four 10GbE Fiber ports, two pair Bypass.
--------------------------	-----------------------------------------------------------------------------------------------------------------

Packing List

1 x PuIM-10G4SF-XL710-BP	1 x L-shaped T10 Plum Wrench
2 x Torx Screws	1 x QIG