


PuIM-2P1M

Two Mini-PCIe and One M.2 Expansion Card Support the Wi-Fi or LTE Module, RoHS



Features

- » Supports 2 x PCIe mini and 1 x 2230/2242 M.2 B key
- » Mini PCIe and M.2 with SIM card slots
- » 2 PCIe 3.0 x4
- » RoHS compliant

Specifications

| Physical Characteristics | |
|--------------------------|---|
| Dimensions (LxWxH) (mm) | 165.50 (L) x 77.8 (W) x 44.2 (H) |
| Storage | |
| Storage | M.2(NGFF) : 1 x M.2(NGFF) 3042/2260 M.2 B key (PCIe/USB2.0(for LTE)/USB3.0) |
| I/O Interface | |
| Expansion | PCI Slot : 2 x mPCIe (PCIe/USB2.0) |
| Wireless | |
| SIM Slot | 4 x SIM card slot |
| Environment | |
| Operating Temperature | 0 ~ 40 °C |
| Humidity | 5% ~ 90% RH, Non-condensing |
| Card Slot Interface | |
| PCIe | 2 PCIe 3.0 x4 |
| Card Features | |
| Controller Chip | ASM1812 (PCIe Gen2x4) |
| | FL1100EX (PCI-E To USB 3.0 (4 Port)) |

Ordering Information

| | |
|---------------|---|
| PuIM-2P1M-R10 | Two Mini-PCIe and One M.2 Expansion Card Support the Wi-Fi or LTE Module. |
|---------------|---|

Packing List

| | |
|-------------------|------------------------------|
| 1 x PuIM-2P1M-R10 | 1 x L-shaped T10 PuIM Wrench |
| 2 x Torx Screws | 1 x QIG |