

# ACE-R4140AP

400 W ATX Mini Redundant Power Supply

## Features

400 W ATX Mini Redundant Power Supply



## Specifications

General	
Dimensions	150 x 85 x 190 (mm)
Efficiency	65%
MTBF	120,000
Operating temperature	0°C ~ 50°C
Output Connector	1 x 20+4-pin ATX, 1 x 4-pin 12V CPU, 8 x HDD/CDROM, 2 x FDD, 2 x SATA, 1 x Buzzer reset, 1 x T.T.L signal, 1 x LED power
Storage temperature	-40°C ~ 70°C
Watt	400W
Input	
Voltage	90 ~ 264 VAC Full Range
Frequency	47 Hz ~ 63 Hz
Input Current	8 A (RMS)@ 100 VAC, 4 A (RMS)@ 240 VAC
Inrush Current	34.4A Max for 100 VAC, 68A Max for 264VAC
Output	
Voltage	+5V/25A, +12V/30A, -12V/0.8A, +3.3V/25A, +5Vsb/2A

## Ordering Information

ACE-R4140AP1-RS	400W AC-DC ATX Redundant module, for ACE-R4140AP, with PFC, CCL; RoHS
ACE-R4140AP-RS	400W ATX Redundant Power Supply, includes two ACE-R4140AP1-RS, with PFC function; CCL