

ACE-R4140AP

400 W ATX Mini Redundant Power Supply

Features

400 W ATX Mini Redundant Power Supply



Specifications

| General | |
|-----------------------|--|
| Dimensions | 150 x 85 x 190 (mm) |
| Efficiency | 65% |
| MTBF | 120,000 |
| Operating temperature | 0°C ~ 50°C |
| Output Connector | 1 x 20+4-pin ATX, 1 x 4-pin 12V CPU, 8 x HDD/CDROM, 2 x FDD, 2 x SATA, 1 x Buzzer reset, 1 x T.T.L signal, 1 x LED power |
| Storage temperature | -40°C ~ 70°C |
| Watt | 400W |
| Input | |
| Voltage | 90 ~ 264 VAC Full Range |
| Frequency | 47 Hz ~ 63 Hz |
| Input Current | 8 A (RMS)@ 100 VAC, 4 A (RMS)@ 240 VAC |
| Inrush Current | 34.4A Max for 100 VAC, 68A Max for 264VAC |
| Output | |
| Voltage | +5V/25A, +12V/30A, -12V/0.8A, +3.3V/25A, +5Vsb/2A |

Ordering Information

| | |
|-----------------|---|
| ACE-R4140AP1-RS | 400W AC-DC ATX Redundant module, for ACE-R4140AP, with PFC, CCL; RoHS |
| ACE-R4140AP-RS | 400W ATX Redundant Power Supply, includes two ACE-R4140AP1-RS, with PFC function; CCL |