

Sistema embedded > Sistema embedded per digital signage > Serie IDS

IDS-200-A70M

AMDR R-series Embedded System, Four independent HDMI™ outputs



Features

- » High Definition AMD® R-series APU
- » Four independent HDMI™ display video outputs
- » Fanless design supporting 0°C ~ 50°C operating temperature
- » SIM card support 3G/LTE wireless connection
- » Support IPMI 2.0 via iRIS-2400 module

Specifications

Color	
Color	Black
Dimensions	
Dimensions	251 x 173.35 x 57
Environment	
Humidity	10% ~ 90%, non-condensing
Operating Temperature	0°C ~ 50°C with air flow
Expansion Slots	
Expansion Slots	PCIe Mini:1 x Full size (supports mSATA), 1 x Half size
Form factor	
SBC Form Factor	CPU:AMD® R-series R-260H 2.1 GHz
	Chipset:AMD® A70M
	System Memory:
	2 x 204-pin DDR3 SO-DIMM (4GB pre-installed)(system max: 16GB)
I/O Interface	
I/O Ports	2 x USB 3.0
	2 x USB 2.0
	Ethernet:
	2 x RJ-45
	1 x PCIe GbE by Intel® I210
	1 x PCIe GbE by Intel® I211
	RS-232:1 x RJ-45
	Display:4 x HDMI™
	Resolution:1920 x 1080@60Hz
	Audio:1 x Line-out, 1 x S/PDIF
	Other:1 x SIM standard card slot
	Wireless:802.11b/g/n 2T2R (optional)
System	
Cooling method / System Fan	Fanless
Drive Bays	1 x 2.5' SATA 6Gb/s HDD/SSD drive bay
Weight	
Weight	5.24 kg/6.5 kg

Ordering Information

IDS-200-A70Mi/4G-R10	Fanless embedded system, AMD APU Dual Core R260H 2.1 GHz, TDP 17W, 4GB DDR3 SO-DIMM (2 x 2GB) pre-installed, 4 x HDMI™, iRIS-2400 optional, 10-30V DC input, R10, RoHS
----------------------	--

Packing List

1 x Power adapter	1 x Wall mount kit
1 x Power cord	1 x Screw pack