

IVS-200-ULT2

Vehicle Surveillance System



Features

- » Intel® i5-5350U dual-core 1.8 GHz CPU or Intel® Celeron® 3755U dual-core 1.7 GHz CPU
- » Four Intel® GbE LAN ports
- » 9 V~36 V DC input
- » Two RS-232/422/485
- » E-Mark certification

Specifications

| | |
|------------------------------|--|
| Form factor | |
| SBC Form Factor | CPU: Intel® Core i5-5350U (dual-core, 1.8 GHz, 15W TDP) or Intel® Celeron® 3765U (dual-core, 1.9 GHz, 15W TDP) |
| | Chipset: SoC |
| | System Memory: 2 x 204-pin DDR3L SO-DIMM. 1 x 4GB pre-installed |
| I/O Interface | |
| I/O Ports | 2 x USB3.0 2 x USB2.0 4 x RJ-45 GbE Lan 2 x DB-9 RS-232/422/485 3 x DB-9 RS-232 (optional) 1 x VGA 1 x HDMI™ 8 bit digital I/O (4-bit input, 4-bit output) (optional) 1 x SIM slot 1 x Line out, 1 x Mic in |
| Expansion Slots | |
| Expansion Slots | 1 x Full size (co-lay mSATA) 1 x Half size |
| System | |
| Cooling method / System Fan | Fanless |
| Drive Bays | 1 x 2.5" SATA 3Gb/s HDD/SSD drive bay |
| Indicator&Buttons | |
| Indicators | HDD/Power |
| Color | |
| Color | Blue C |
| Dimensions | |
| Dimensions | 255 x 63 x 150 |
| Weight | |

| | |
|-----------------------|----------------------------|
| Weight | 2.2 kg/3 kg |
| Environment | |
| Operating Temperature | -20°C ~ 60°C with air flow |
| Humidity | 5% ~ 95%, non-condensing |

Ordering Information

| | |
|------------------------|---|
| IVS-200-ULT2-i5/4G-R10 | Fanless System with Intel® Core™ i5-5350U up to 2.9GHz, TDP 15W, 4 x GbE LAN port , 1 x HDMI™, 1 x VGA, 2 x RS-232/422/485, 1 x 2.5" removable SATA HDD bay, 4G memory pre-installed, 9~36V DC, R10, RoHS |
| IVS-200-ULT2-C/4G-R10 | Fanless System with Intel® Celeron® 3765U 1.7GHz, TDP 15W, 4 x GbE LAN port , 1 x HDMI™, 1 x VGA, 2 x RS-232/422/485, 1 x 2.5" removable SATA HDD bay, 4G memory pre-installed, 9~36V DC, R10, RoHS |