

DM2-W215

21.5" Latest Generation Industrial Monitor



Features

- » Front OSD, easy access for setting adjustment
- » Speakers positioned at the front, ensuring clear sound delivery even in panel mount
- » Supports gloved operation and waterproof protection
- » Built-in camera, ideal for AI facial recognition
- » USB 3.2 Gen1 Type-A supports 10W
- » IP65 compliant front panel with aluminum frame
- » Anti-glare and anti-UV PCAP

Specifications

Display	
LCD Size	21.5" (16:9)
Brightness(cd/m2)	350
Max Resolution	1920 x 1080
Contrast Ratio	1000:1
Backlight MTBF(hrs)	50000
I/O Interface	
I/O Ports	1 x VGA (DB-15)
	1 x HDMI
	1 x DisplayPort1.2
	1 x USB 3.2 Gen1 Type-B
	4 x USB 3.2 Gen1 Type-A (5V2A) (Lite without)
	1 x Line out
	1 x 9V-36V DC jack
	1 x 3-pin terminal block
Power	
Power adapter	12V DC
Environment	
Operating Temperature	0°C ~ 50°C
Humidity	10% to 95%@40°C (non-condensing)
Storage Temperature	-20°C ~ 60°C
IP Level	IP 65 compliant front panel
Physical Characteristics	
Color	Black + Silver
Dimensions (LxWxH) (mm)	519.40 x 327.00 x 50.50
Cutout Dimensions	501.00 x 302.00
LCD	
LCD Color	16.7M
Viewing Angle (H-V)	178°/178°
Touch	
Touch Screen	10-point Projected capacitive touch window (Anti-UV, Anti-glare Surface)
Touch Controller	Capacitive:litek

Ordering Information

DM2-W215K-R10	21.5" 350 cd/m ² 1920 x 1080 monitor, VGA, HDMI, DisplayPort, with USB 3.0 HUB, USB PC touch screen, 9 ~36V DC input, Speaker, Camera, R10
DM2-W215KL-R10	21.5" 350 cd/m ² 1920 x 1080 monitor, VGA, HDMI, DisplayPort, USB PC touch screen, 9 ~36V DC input, Lite, R10

Packing List

1 x DM2-W215	1 x USB-touch Cable
1 x 3-pin Terminal Block	4 x VESA Screws
11 x Panel Mount Kit	