

TANK-6000-C226

Support IPMI 2.0 via IEI iRIS solution, Intel® E3 1225 v3/i3 4330 high performance CPU



Features

- » Workstation with Intel® C226 chipset
- » Intel® E3 1225 v3/i3 4330 high performance CPU
- » Support two PCIe by 8 expansion cards
- » 4 x LAN port (two SFP fiber combo ports)
- » 3 x 2.5" HDD/SSD bay
- » Support IPMI 2.0 via IEI iRIS solution
- » Support programable OLED display module

Specifications

| | |
|-----------------------------|---|
| Color | |
| Color | Black |
| Dimensions | |
| Dimensions | 310 x 199.5 x 112 |
| Environment | |
| Humidity | 5% ~ 95%, non-condensing |
| Operating Temperature | -20°C ~ 55°C with air flow (SSD) |
| Expansion Slots | |
| Expansion Slots | PCIe: 2 x PCIe x8 (Gen 3) |
| Form factor | |
| SBC Form Factor | CPU: |
| | Intel® Xeon® E3 1225-v3 3.2 GHz |
| | Intel® Core™ i3 4330 3.5 GHz |
| | Chipset: Intel® C226 |
| | System Memory: |
| | 4 x 240-pin DDR3 U-DIMM, 4 GB pre-installed (system max: 32 GB) |
| I/O Interface | |
| I/O Ports | 4 x USB 3.0 |
| | 2 x USB 2.0 |
| | Ethernet: |
| | 4 x RJ-45 |
| | 1 x PCIe GbE by Intel® i217 PHY |
| | 3 x PCIe by GbE Intel® i210 |
| | Fiber: |
| | 2 x Combo (SFP Fiber/RJ-45), combo with LAN 1/LAN 2 |
| | COM Port: 2 x RS-232 (DB-9) |
| | Display: 1 x HDMI™, 1 x VGA |
| | Resolution: |
| | HDMI™: Up to 1920 x 1200@60Hz |
| | VGA: Up to 1920 x 1200@60Hz |
| | Audio: 1 x Line-out, 1 x Mic in |
| System | |
| Cooling method / System Fan | 92 mm x 92 mm x 25 mm |
| Drive Bays | 3 x 2.5' SATA 6Gb/s HDD/SSD drive bay |
| Weight | |

| | |
|--------|---------------|
| Weight | 2.5 kg/4.6 kg |
|--------|---------------|

Ordering Information

| | |
|---------------------------|--|
| TANK-6000-C226i-i3/4G-R11 | Embedded System with Intel C226 chipset, Intel dual-core i3- 4330 3.5GHz ,TDP 54W,OLED indicator, 2 x PCIe by 8 expansion, 3 x 2.5" SATA HDD bay,DDR3 U-DIMM 4GB pre-installed (2 x 2GB), iRIS-2400 supported, 19/24V DC,RoHS |
| TANK-6000-C226i-E3/4G-R11 | Embedded System with Intel C226 chipset, Intel quad-core Xeon E3-1225 v3 3.2GHz ,TDP 84W,OLED indicator, 2 x PCIe by 8 expansion, 3 x 2.5" SATA HDD bay,DDR3 U-DIMM 4GB pre-installed (2 x 2GB) , iRIS-2400 supported, 19/24V DC, RoHS |

Packing List

| | |
|--|--------------------|
| 1 x Power Adapter (With PSE & ErP Certified) | 1 x Wall mount kit |
| 1 x Screw pack | |