

PuIM-10G2SF

Intel® Ethernet Controller X710-BM2 based Network Interface Card with 2 x SFP+ by PCIe 3.0 x8 interface



Features

- 1 x Intel® Ethernet Controller X710-BM2
- 2 x 10 GbE SFP+ connectors
- PCIe 3.0 x8
- RoHS compliant

Specifications

| | |
|--------------------------|-------------------------------------|
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 165.50 (L) x 77.8 (W) x 44.2 (H) |
| I/O Interface | |
| Ethernet | 2 x SFP+ |
| Environment | |
| Operating Temperature | 0°C ~ 40°C (32°F ~ 104°F) |
| Storage Temperature | -20°C ~ 75°C (-4°F ~ 167°F) |
| Humidity | 5%~90% RH, Non-condensing |
| Certifications | |
| Safety & EMC | RoHS |
| Card Slot Interface | |
| PCIe | PCIe 3.0 x8 |
| Card Features | |
| Speed | 1GbE/10GbE |
| Controller Chip | Intel® Ethernet Controller X710-BM2 |

Ordering Information

| | |
|----------------------|--|
| PuIM-10G2SF-X710-R10 | Intel® Ethernet Controller X710-BM2 based Network Interface Card with 2x SFP+ by 1 PCIe 3.0 x 8 interface. |
|----------------------|--|

Packing List

| | |
|-----------------------------|------------------------------|
| 1 x PuIM-10G2SF-X710 module | 1 x L-shaped T10 Plum Wrench |
| 2 x Torx Screws | 1 x QIG |