


ICE-DB-T6R

Baseboard for COM Express Type 6 Module COM.0 Rev. 2.1



Features

- » Intel® 22nm Atom™ or Celeron® on-board SoC supported
- » Intel® HD Graphics Gen7 integrates high-performance graphics and media processing
- » Supports 1333/1066 MHz DDR3L (1.35V) memory, up to 8 GB
- » Supports one analog CRT, one 24-bit dual-channel LVDS, and one DDI
- » Optional soldered down 4 GB SSD
- » IEI One Key Recovery solution allows you to create rapid OS backup and recovery

Specifications

Storage	
Storage	4 x SATA 1 x SD/MicroSD card
I/O Interface	
Display Output	1 x VGA 2 x Display Port 1 x LVDS :18/24-bit single or dual-channel (with PWM back light controller) 1 x iDP
Audio	Description: Realtek ALC662 HD Audio codec 1 x Line in :on rear IO 1 x Line out :on rear IO 1 x Mic :on rear IO 1 x Front Audio :2x5 pin
I/O Interface	1 x PS/2
Expansion	1 x PCIe x16 1 x PCIe x4 5 x PCIe x1 2 x PCIe mini Card Slot :with mSATA support,colay with SATA 4
Other Features	
TPM	2x10 pin

Ordering Information

ICE-DB-T6R-R10	Base Board for COM Express Type 6 Module COM.0 Rev. 2.1,support PICMG EAPI R1.0
----------------	---