

# AFL3P-W10MSR-U

Magnetic card reader with mounting bracket



## Features

- » Magnetic card reader with mounting bracket
- » Scan Rate: 100-1000mm/sec
- » Magnetic Card: IISO 7810-7813 and JISII
- » Tracks T1&T2&T3: Decording Density T1/T2/T3: 210/75/210 BPI Capacity T1/T2/T3: 79/40/107 Characters
- » Life Cycle: 300,000 passes

## Specifications

|                       |   |
|-----------------------|---|
| Environment           |   |
| Operating Temperature | 0°C ~ 50°C  |
| Storage Temperature   | -20°C ~ 70°C  |
| Input                 |   |
| Voltage               | 5V DC USB   |
| General               |   |
| MTBF                  | 24,000 hours  |
| Dimensions            | 90.0mm X 29.00mm X 38.00mm  |
| Material              |   |
| Material              | Plastic   |
| Weight                |   |
| Weight                | 61.2 g (net weight)   |
| Key Features          |   |
| Key Features          | Magnetic card reader with mounting bracket  |
|                       | Scan Rate: 100-1000mm/sec   |
|                       | Magnetic Card: IISO 7810-7813 and JISII   |
|                       | Tracks T1&T2&T3: Decording Density T1/T2/T3: 210/75/210 BPI Capacity T1/T2/T3: 79/40/107 Characters |
|                       | Life Cycle: 300,000 passes  |

## Ordering Information

|                    |   |
|--------------------|---|
| AFL3P-W10MSR-U-R10 | Magnetic card reader with USB interface, for AFL3-08A-BT/AFL3-W10A-BT/AFL3-12A-BT/AFL3-W15A-BT/AFL3-W15B-H81, R10 |
|--------------------|---|