


IMB-Q470

Micro-ATX motherboard supports LGA1200 Intel® 10th/11th Gen. Core™ i9/i7/i5/i3, Pentium® and Celeron® processor, DDR4, triple displays, dual LAN, M.2, 8 USB 3.2, 6 USB 2.0, 10 COM, SATA 6Gb/s, HD Audio and RoHS



Features

- » LGA1200 Intel® 10th/11th Generation Core i9/i7/i5/i3, Pentium and Celeron processor (up to 125W)
- » Two 288-pin 2933 MHz unbuffered DDR4 SDRAM DIMM slots (system max. 64GB)
- » Support triple independent display via DVI, VGA and internal DP++
- » Support one PCIe x16 and two PCIe x4 expansions
- » Support one M.2 B key, one M.2 M key and four SATA for storage

Specifications

| | |
|-----------------------------|---|
| Form Factor | |
| Form Factor | micro ATX |
| System | |
| CPU | LGA1200 socket supports 10th/11th generation Intel® Core™ i9/i7/i5/i3, Pentium® or Celeron® processor. up to 125W TDP |
| Chipset | Intel® Q470/Q470E |
| Memory | Two 288-pin 2933 MHz unbuffered DDR4 SDRAM DIMM slots (supporting up to 64 GB memory) |
| Memory Max. | 64GB |
| Cooling method / System Fan | 1 x CPU fan connector (1x4 pin) 1 x System fan connector (1x4 pin) |
| Physical Characteristics | |
| Dimensions (LxWxH) (mm) | 244mm x 244mm |
| Net Weight | 700g |
| Storage | |
| Storage | 4 x SATA : RAID 0/1/5/10 supported 1 x M.2(NGFF) : B key 2242/2280 (PCIe Gen3 x2) |
| I/O Interface | |
| Display Output | 1 x VGA : up to 1920 x 1080@60Hz 1 x DVI-D : up to 2560 x 1600@60Hz 1 x DP++ : up to 3840 x 2160@60Hz |
| Ethernet | 2 x LAN - LAN1: Intel® I219-LM GbE controller LAN2: Intel® I225V/I226V GbE controller |
| Audio | 1 x HD Audio : Realtek ALC888S HD Audio codec - 3 x Audio jack (Line-in, Line-out, Mic-in) - 1 x Analog audio (2x5 pin) |

| | |
|-----------------------|--|
| I/O Interface | 10 x Internal RS-232 - 2 x 2*20-pin, P=2.54 2 x 2*5 pin, P=2.54 6 x External USB 2.0 : Type A 8 x External USB 3.2 Gen1x1 : 5 Gb/s(Type A) 1 x PS/2 : for KB/MS 1 x LPT : 2*13 pin |
| Expansion | 1 x PCIe x16 : Gen4 slot with x16 Signal 2 x PCIe x4 : Gen4 open-end 2 x M.2(NGFF) - 1 x M.2 B key 2242/2280 (PCIe Gen3 x2) 1 x M.2 M key 2242/2280 (PCIe Gen3 x4) |
| Power | |
| Power Consumption | » 3.3V@1.13A, 5V@10.14A, 12V@11.86A, 5VSB@0.23A (11th Gen.Intel® Core® i9-11900K 3.50 GHz 125W CPU with 32GB 2933MHz DDR4 memory, EUP enabled) » 3.3V@1.16A, 5V@10.45A, 12V@5.93A, 5VSB@0.26A (10th Gen.Intel® Core® i9-10900E 2.80 GHz 65W CPU with 32GB 2933MHz DDR4 memory, EUP enabled) |
| Power Supply | ATX/AT power supply Support AT/ATX mode ErP/EuP Compliant |
| Environment | |
| Operating Temperature | -10°C~60°C |
| Storage Temperature | -30°C~70°C |
| Humidity | 5% ~95%, non-condensing |

Ordering Information

| | |
|--------------|---|
| IMB-Q470-R11 | Micro-ATX motherboard supports LGA1200 Intel® 10th/11th Gen. Core™ i9/i7/i5/i3, Pentium® and Celeron® processor, DDR4, triple displays, dual 2.5GbE LAN, M.2, 8 USB 3.2, 6 USB 2.0, 10 COM, SATA 6Gb/s, HD Audio and RoHS |
|--------------|---|

Packing List

| | |
|------------------------------------|----------------|
| 1 x IMB-Q470 single board computer | 2 x SATA cable |
| 1 x I/O shielding | 1 x QIG |